

Precision Ground Rod, Cut to Length, With Chamfer

Inch Sizes 3/32" to 1-1/4" Diameter

h6 Tolerances

OD(Inches)	OD (Inches)	L (Inches)	Item No.	OD(Inches)	OD (Inches)	L (Inches)	Item No.
3/32	0.0938	3	GR55001	7/16	0.4375	4	GR55033
1/8	0.1250	1 1/2	GR55002	7/16	0.4375	4 1/2	GR55034
1/8	0.1250	2	GR55003	7/16	0.4375	5	GR55035
1/8	0.1250	2 1/2	GR55004	7/16	0.4375	6	GR55036
1/8	0.1250	3	GR55005	1/2	0.5000	2 1/2	GR55037
1/8	0.1250	4	GR55006	1/2	0.5000	3	GR55038
1/8	0.1250	6	GR55007	1/2	0.5000	3 1/2	GR55039
3/16	0.1875	2	GR55008	1/2	0.5000	4	GR55040
3/16	0.1875	2 1/2	GR55009	1/2	0.5000	5	GR55041
3/16	0.1875	3	GR55010	1/2	0.5000	6	GR55042
3/16	0.1875	4	GR55011	9/16	0.5625	3 1/2	GR55043
3/16	0.1875	6	GR55012	9/16	0.5625	4	GR55044
1/4	0.2500	2	GR55013	9/16	0.5625	6	GR55045
1/4	0.2500	2 1/2	GR55014	5/8	0.6250	3	GR55046
1/4	0.2500	3	GR55015	5/8	0.6250	3 1/2	GR55047
1/4	0.2500	4	GR55016	5/8	0.6250	4	GR55048
1/4	0.2500	5	GR55017	5/8	0.6250	5	GR55049
1/4	0.2500	6	GR55018	5/8	0.6250	6	GR55050
5/16	0.3125	2	GR55019	3/4	0.7500	3	GR55051
5/16	0.3125	2 1/2	GR55020	3/4	0.7500	4	GR55052
5/16	0.3125	3	GR55021	3/4	0.7500	4 1/2	GR55053
5/16	0.3125	4	GR55022	3/4	0.7500	5	GR55054
5/16	0.3125	6	GR55023	3/4	0.7500	6	GR55055
3/8	0.3750	2	GR55024	7/8	0.8750	3	GR55056
3/8	0.3750	2 1/2	GR55025	7/8	0.8750	4	GR55057
3/8	0.3750	3	GR55026	7/8	0.8750	5	GR55058
3/8	0.3750	3 1/2	GR55027	1	1.0000	3	GR55059
3/8	0.3750	4	GR55028	1	1.0000	4	GR55060
3/8	0.3750	6	GR55029	1 1/4	1.2500	4 1/2	GR55061
7/16	0.4375	2 1/2	GR55030	1 1/4	1.2500	6	GR55062
7/16	0.4375	2 3/4	GR55031	1 1/2	1.5000	6	GR55063

Grounded Rod, Random Lengths RR

Inch Sizes 1/16" to 1-1/2" Diameter

OD(Inches)	OD (Inches)	L (Inches)	Item No.	Tolerances, inch		
1/16	0.0625	12 1/5	GRR-4	Sizes D in inch	D, h6	L
3/32	0.0938	12 1/5	GRR-6	1/16 to 7/64	+0, -.00024	+0~0.25
1/8	0.1250	12 1/5	GRR-8	1/8 to 7/32	+0, -.00031	+0~0.25
3/16	0.1875	12 1/5	GRR-12	1/4 to 3/8	+0, -.00035	+0~0.25
1/4	0.2500	12 1/5	GRR-16	7/16 to 5/8	+0, -.00043	+0~0.25
5/16	0.3125	12 1/5	GRR-20	3/4 to 1	+0, -.00051	+0~0.25
3/8	0.3750	12 1/5	GRR-24	1-1/4 to 1-1/2	+0, -.00063	+0~0.25
7/16	0.4375	12 1/5	GRR-28			
1/2	0.5000	12 1/5	GRR-32	TOLERANCES, inch		
9/16	0.5625	12 1/5	GRR-36	Sizes, inch	Straightness	Roundness
5/8	0.6250	12 1/5	GRR-40	1/16 to 3/16	.006 max	.00008 max
7/8	0.8750	12 1/5	GRR-56	13/64 to 3/8	.006 max	.00016 max
1	1.0000	12 1/5	GRR-64	7/16 to 1/2	.004 max	.00016 max
1 1/4	1.2500	12 1/5	GRR-80	9/16 to 1-1/2	.003 max	.00016 max
1 1/2	1.5000	12 1/5	GRR-96			

Unground Rod, Random Lengths RR

Inch Sizes 1/16" to 1-1/2" Diameter

OD(Inches)	OD (Inches)	L (Inches)	Item No.	Tolerances, inch		
1/16	0.0625	12 1/5	RR-4	D	L	
3/32	0.0938	12 1/5	RR-6	+0~+0.015"	+0~+0.5"	
1/8	0.1250	12 1/5	RR-8			
3/16	0.1875	12 1/5	RR-12	Tolerances, inch		
1/4	0.2500	12 1/5	RR-16	Sizes in inch	Straightness	Roundness
5/16	0.3125	12 1/5	RR-20	1/16~7/32	.016 max	.004 max
3/8	0.3750	12 1/5	RR-24	15/64~27/64	.010 max	.004 max
7/16	0.4375	12 1/5	RR-28	7/16~1	.010 max	.004 max
1/2	0.5000	12 1/5	RR-32			
9/16	0.5625	12 1/5	RR-36			
5/8	0.6250	12 1/5	RR-40			
7/8	0.8750	12 1/5	RR-56			
1	1.0000	12 1/5	RR-64			
1 1/4	1.2500	12 1/5	RR-80			
1 1/2	1.5000	12 1/5	RR-96			